



EWK 1000 PLUS

Compact checkweigher –
the economical solution

EWK 1000 PLUS

The EWK 1000 PLUS checkweigher is designed for checking the weights, nominal quantities filled and the completeness of prepackaged products.

EWK 1000 PLUS features a built-in Sartorius strain-gauge type load cell specially developed for checkweighing. Low space requirements, a transport height that can be adjusted whenever needed and a program-controlled belt speed enable the EWK 1000 PLUS to be used in many areas of production.

The systematic, hygienic design concept along with sleek, polished stainless steel surfaces as well as the self-supporting stainless steel weighing and transport system with a high clearance from the floor all make this checkweigher exceptionally easy to clean.

The quick unlocking device lets you effortlessly exchange the weigh belt in just seconds. An interface port enables weights to be transferred to applications for further processing. This capability makes it easy to integrate the EWK 1000 PLUS into statistical quality control systems, such as Sartorius ProControl for Windows® (SPCfWin).

Performance features

- Sorting into up to 5 classes
- Automatic zeroing
- Pneumatic pusher or airblast nozzle ejector
- Memory for 100 products
- Choice of dialogue languages
- Password protection
- Easy, context-sensitive operator prompting
- User-programmable joker key
- Fast belt change-out without the need for tools
- Stainless steel stand enclosure, IP65 protection
- Hygienically optimized design for simple and thorough cleaning
- Bright, high-contrast liquid-crystal display
- Program-controlled, continuously adjustable belt speed
- Maintenance-free, electronically commutated motors

Functional expansions

- Verifiable as legal for trade according to OIML-R51
- RS-232C interface port for external printer (printer not part of the standard equipment supplied)
- Thermal tape printer in stainless steel enclosure; built onto the control panel
- Trend controller for controlling filling and portioning
- Can be connected to external evaluation systems, especially Sartorius ProControl for Windows®



Sartorius Aachen GmbH & Co KG
Am Gut Wolf 11
52070 Aachen, Germany
Phone +49.241.1827.0
Fax +49.241.1827.210
www.sartorius.com

Specifications subject to change without notice.
Printed in Germany on paper that has been
bleached without any use of chlorine.
W/sart-000 - G
Publication No.: BOE1007-e05091
Order No.: 98649-005-89