

MCW "PROFESSIONAL" SERIES CRANE SCALES



Reliable and easy to use AISI 304 stainless steel crane scales suitable for indoor and outdoor use, for industrial weighing applications. Reduced lifting distance of the crane. IP67 protection from dust and rain. Available also CE-M APPROVED. Fitted with test certificate obtained with sample weights.

MAIN FEATURES

- Large backlit 25mm LCD display easily visible in all lighting conditions and also with low temperatures.
- Fitted with standard approved upper galvanized shackle and standard approved bottom swivelling hook.
- Reduced distance between the upper shackle and bottom hook.
- Precision: +/- 0.03% F.S.
- Waterproof keyboard with 5 keys: ZERO, AUTOMATIC TARE, MODE, PRINT, and ON/OFF.
- MODE-key configurable as:
PEAK (maximum value read), HOLD (blocking the weight viewed), Weighs accumulation, lb/kg/N conversion.
 See the user manual for the list of the functions.
- IP67 stainless steel case (dust and rain).
- Fitted with remote control for up to a 8 m distance. The remote control may be configured by the customer as automatic tare only, or as a remote keypad.
- Rechargeable sealed battery with a 40-hour life battery. On request, it is available a second battery for a 24/24h use.
- Equipped with 230Vac 50 Hz battery charger.
- Operating temperature: -10 /+40 °C.
- Programmable digital filter and auto switch-off.

AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- **Infrared remote control** (standard), operating up to 8m: zero; tare / manual tare; enable / disable function; print; switch-off.
- **Radiofrequency 6-key remote control** (optional) operating up to 50m: zero; tare; enable / disable function; print; switch-off.

OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- DOT red LED display of 40mm.
- RF weight transmission to remote indicator up to over 70m indoors, 150m outdoors, adequate environmental and installation conditions.
- WI-FI interface.
- Attached thermal printer option box or virtual and integrated printer.
- Integrated thermal printer (code TPRPR2 only for the "R2").
- Remote weight indicator (see DFW., 3590., TRS., DGT60.. Series' indicators) with printer connected through radio frequency
- 433MHz radiofrequency remote control (compatible with remote indicator).
- SIT calibration certificate according to OIML/ASTM standards.

Crane scales MCW and MCWR2

WEIGHTS OF THE CRANE SCALES

Code	Weight (including packing)
MCW150	10 kg
MCW300	10 kg
MCW600	10 kg
MCW1500	16 kg
MCW3000	16 kg
MCWT6	16 kg

MCW Crane scales: Available versions

Code	Max Capacity kg	Standard Division Kg	HR Division kg	CE-M Division kg
MCW150R2	150	0,05	0,02	
MCW300R2	300	0,1	0,05	
MCW600R2	600	0,2	0,1	
MCW1500R2	1500	0,5	0,2	
MCW3000	3000	1	0,5	
MCWT6	6500	2	1	
MCW150MR2 M	150			0,05
MCW300MR2 M	300			0,1
MCW600MR2 M	600			0,2
MCW1500MR2 M	1500			0,5
MCW3000M M	3000			1
MCWT6M M	6000			2

Options only available at time of order

Code	Description
EHR	High resolution model for internal factory use.
OBTPRI	Thermal printer for mounting attached to weight indicator, with stainless steel case, connection cable, power supply from weight indicator. Combinable with stainless steel indicators.
OBBMCI	Memory Data Printer for mounting attached to weight indicator, with stainless steel case, connection cable, memory card, power supply from weight indicator. Combinable with stainless steel indicators.
TPRPR2	Thermal printer integrated to the crane scale (only for the "MCW...R2" models), fitted with connection cable and power supply from the instrument.
WIFIT	WI-FI interface for wireless connection (through access point) to the company computer system.
RFITR	Integrated 868 MHz radio frequency module on the indicator, complete of RS232 port. Max. functioning distance in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. Up to 50 configurable channels. (RFITR must be combined with another radio module).
OBRFUSB	868 MHz radio frequency module for PC, with PVC box and 1 m USB/mini USB connecting cable; power supply directly from the USB port. Max. functioning distance, in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. 50 configurable channels. (OBRFUSB must be combined with another radio module).
OBRF232	868 MHz radio frequency module for PC, with PVC box, 3 m RS232 connecting cable complete with DB9 pin connector and power supply. Max. functioning distance, in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. 50 configurable channels. (OBRF232 must be combined with another radio module).
TLR	433MHz radio frequency remote control, with 6 keys, for use up to 50 m of distance, in appropriate environmental conditions.
DFCLK	Real time clock for printing/displaying of the date and time.
ALMEM	Alibi memory (fiscal memory, max 120.000 weighs) for approved transmission of the weight to PC/PLC. Real time clock integrated for print of the date/time.
MCWLB	Version with 40mm red led digits (10/15 hour battery operating time).
MCWBK	Kit for using the scale 24/7 made up of extractable battery, additional extractable battery and device for the recharge with status indication (to be used with the charger fitted with the scale).
EEAC	SIT/ASTM calibration certificate for crane scales with capacity greater than 1500 kg. NET PRICE

Indicator connectable with MCW through optional radio transmission

Code	Description
DFWPM	Portable weight repeater for radio frequency communication, with ABS case, 5-key keypad and backlit LCD display.
DFWPM10USB	Portable weight repeater for radio frequency communication, with ABS case, 5-key keypad and backlit LCD display. Fitted with USB port and memory for saving the weighs.
DFW06XPCC	Multifunction weight indicator with IP65 ABS case, 5-key keypad, backlit LCD display, and standard weighing programme (not including the repeater modes).
DFWK06PXPC	Multifunction weight indicator with IP65 ABS case, 17-key keypad, backlit LCD display, attached thermal printer, and standard weighing programme (not including the repeater modes).
DGT60R	Weight repeater with IP68 stainless steel case, 5-key keypad, 60 mm LED display and dedicated program (not including the weighing functions).
MSTSLV	Optional program for using the indicator as a universal weight repeater or as a multi-scale repeater (MASTER) in combination with the DFW/DGT/MCW (this option does not include the weighing functions).
OBRF	External 868 MHz radio frequency module for weight indicator/repeater, with ABS IP65 protecting box and 3 m RS232 connecting cable; power supply from weight indicator/repeater. Max. functioning distance, in appropriate environmental and installation conditions: 70m indoors, 150m outdoors. 50 configurable channels. (OBRF must be combined with another radio module).
DFCLK	Real time clock for printing/displaying of the date and time.

Accessories

Code	Description
GG15	Swivelling bottom hook with safety lock 15 t.
GG22	Swivelling bottom hook with safety lock 22 t.
GG30	Swivelling bottom hook with safety lock 30 t.
CA2	Connection ring 2,5 t.
CA4	Connection ring 4 t.
CA8	Connection ring 8 t.
CA15	Connection ring 15 t.
CA30	Connection ring 30 t.
DFTL10	Infrared remote control, with 18 keys, for use up to 8 m of distance.
UKPLUG	Power adapter from Schuko to BS1363.
TECMAN	Printed technical manual (free, if downloaded from the web). NET PRICE.
UMAN	Printed user manual (free, if downloaded from the web and available in the CD, fitted with the product). NET PRICE.

MEASUREMENTS OF HOOKS IN mm

	Code	A	B	C	D	H
	GG15	95	354	96	455	63
	GG22	121	432	120	565	80

MEASUREMENTS OF RINGS IN mm

	Code	A	B	C
	CA2	86	60	110
	CA4	111	75	135
	CA8	152	100	180
	CA15	174	110	200

	GG30	133	568	139	667	88
--	-------------	-----	-----	-----	-----	----

	CA30	270	180	340
---	-------------	-----	-----	-----